

TEST REPORT

Report Reference No.: HK2605280558-2EH

Compiled by

(position+printed name+signature)...: Testing engineer Len Liao




Supervised by

(position+printed name+signature)...: Technique principal Sliver Wan



Approved by

(position+printed name+signature)...: Manager Jason Zhou



Date of issue: 2026/07/07

Testing Laboratory Name : Shenzhen HUAKE Testing Technology Co., Ltd.

Address: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park,
Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

Applicant's name : EDA Technology Shanghai Co.,Ltd

Address: Building 29, Shengchuang Enterprise Park, No.1661 Jialuo Road,
Jiading District, Shanghai, PRC

Test specification :

Standard : EN IEC 62311:2020

TRF Originator : Shenzhen HUAKE Testing Technology Co., Ltd.

Master TRF : Dated 2020-05

Shenzhen HUAKE Testing Technology Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen HUAKE Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen HUAKE Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Product Name : ED-CM0NANO

Trade Mark: EDATEC

Product Model: ED-CM0NANO

Series Model: N/A

Hardware Version : V1

Software Version: V1

Ratings: DC 4.75V - 5.25V

Result: Pass

TEST REPORT

Test Report No. :	HK2605280558-2EH	2026/07/07
		Date of issue

Product Name : ED-CM0NANO

Product Model : ED-CM0NANO

Series Model : N/A

Applicant : EDA Technology Shanghai Co.,Ltd

Address : Building 29, Shengchuang Enterprise Park, No.1661 Jialuo Road,
Jiading District, Shanghai, PRC

Manufacturer : EDA Technology Shanghai Co.,Ltd

Address : Building 29, Shengchuang Enterprise Park, No.1661 Jialuo Road,
Jiading District, Shanghai, PRC

**** Issued History ****

Revision	Description	Issued Date	Remark
Revision 1.0	Initial Test Report Release	2026/07/07	Jason Zhou

Table of Contents

Page

1 . GENERAL INFORMATION	5
1.1 GENERAL REMARKS	5
1.2 GENERAL DESCRIPTION OF EUT	6
2 . EN IEC 62311 REQUIREMENT	7
2.1 GENERAL INFORMATION	7
2.2 LIMIT	7
3. RESULT	8



HUAKE TESTING

1. GENERAL INFORMATION

1.1 GENERAL REMARKS

Date of receipt of test sample	:	2026/05/28
Testing commenced on	:	2026/05/28
Testing concluded on	:	2026/07/07

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Shenzhen HUAKE Testing Technology Co., Ltd. Tel.: +86-0755-2302 9901 E-mail: info@huak.com Web.: www.huak.com
Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

1.2 GENERAL DESCRIPTION OF EUT

Equipment	ED-CM0NANO																								
Model Name	ED-CM0NANO																								
Series Model	N/A																								
Difference description	N/A																								
Product Description	The EUT is ED-CM0NANO. BT-EDR: <table border="1"> <tr> <td>Operation Frequency:</td><td>2402 MHz ~ 2480 MHz</td></tr> <tr> <td>Modulation Type:</td><td>GFSK, $\pi/4$DQPSK, 8DPSK</td></tr> <tr> <td>Antenna Designation:</td><td>External Antenna</td></tr> <tr> <td>Antenna Gain(Peak)</td><td>3.7dBi</td></tr> </table> BT-BLE: <table border="1"> <tr> <td>Operation Frequency:</td><td>2402 MHz ~ 2480 MHz</td></tr> <tr> <td>Modulation Type:</td><td>GFSK</td></tr> <tr> <td>Antenna Designation:</td><td>External Antenna</td></tr> <tr> <td>Antenna Gain(Peak)</td><td>3.7dBi</td></tr> </table> 2.4G Wifi <table border="1"> <tr> <td>Operation Frequency:</td><td>IEEE 802.11b/g/n HT20: 2412-2472MHz</td></tr> <tr> <td>Modulation Type:</td><td>DSSS, OFDM</td></tr> <tr> <td>Antenna Designation:</td><td>External Antenna</td></tr> <tr> <td>Antenna Gain(Peak)</td><td>3.7dBi</td></tr> </table> Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.	Operation Frequency:	2402 MHz ~ 2480 MHz	Modulation Type:	GFSK, $\pi/4$ DQPSK, 8DPSK	Antenna Designation:	External Antenna	Antenna Gain(Peak)	3.7dBi	Operation Frequency:	2402 MHz ~ 2480 MHz	Modulation Type:	GFSK	Antenna Designation:	External Antenna	Antenna Gain(Peak)	3.7dBi	Operation Frequency:	IEEE 802.11b/g/n HT20: 2412-2472MHz	Modulation Type:	DSSS, OFDM	Antenna Designation:	External Antenna	Antenna Gain(Peak)	3.7dBi
Operation Frequency:	2402 MHz ~ 2480 MHz																								
Modulation Type:	GFSK, $\pi/4$ DQPSK, 8DPSK																								
Antenna Designation:	External Antenna																								
Antenna Gain(Peak)	3.7dBi																								
Operation Frequency:	2402 MHz ~ 2480 MHz																								
Modulation Type:	GFSK																								
Antenna Designation:	External Antenna																								
Antenna Gain(Peak)	3.7dBi																								
Operation Frequency:	IEEE 802.11b/g/n HT20: 2412-2472MHz																								
Modulation Type:	DSSS, OFDM																								
Antenna Designation:	External Antenna																								
Antenna Gain(Peak)	3.7dBi																								
Channel List	Refer to below																								
Hardware Version	V1																								
Software Version	V1																								
Note:	For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.																								
Note: Antenna gain Refer to the antenna specifications. The cable loss data is obtained from the supplier. The test results in the report only apply to the tested sample.																									

2. EN IEC 62311 REQUIREMENT

2.1 GENERAL INFORMATION

According to its specifications, the EUT must comply with the requirements of the following standards:

EN IEC 62311:2020[Assessment of the compliance of low power electronic and electrical equipment with the basic restrictions related to human exposure to electromagnetic fields (0 Hz to 300 GHz)]

2.2 LIMIT

A. Typical usage, installation and the physical characteristics of equipment make it inherently compliant with the applicable EMF exposure levels such as those listed in the bibliography. This low-power equipment includes unintentional (or non-intentional) radiators, for example incandescent light bulbs and audio/visual (A/V) equipment, information technology equipment (ITE) and multimedia equipment (MME) that does not contain radio transmitters.

NOTE Equipment is described as A/V equipment, ITE or MME if its main use is playback/recording of music, voice or images, or processing of digital information.

B. The input power level to electrical or electronic components that are capable of radiating electromagnetic energy in the relevant frequency range is so low that the available antenna power and/or the average total radiated power cannot exceed the low-power exclusion level defined in 4.2.

C. The available antenna power and/or the average total radiated power are limited by product standards for transmitters to levels below the low-power exclusion level defined in 4.2.

D. Measurements or calculations show that the available antenna power and/or the average total radiated power are below the low-power exclusion level defined in 4.2.



HUAK TESTING

3. RESULT

See Test report 25031202-45430-0 for test data.

.....**End of Report**.....